

The Dishwashing Machine Specialists

PROJECT: _		
ITEM #	ç	TY:
MODEL #		
AIA #	SIS #	

# **44 PRO-E**

# HIGH TEMPERATURE ELECTRIC RACK CONVEYOR



Rendered image is for general visual representation only. Please refer to specifications for the latest detailed product information









### STANDARD FEATURES

- **Perpetual Rack Advance System** with digital jam monitoring, and mechanical drive protection
- **Automated Delime Function** with user-customizable alert intervals
- 209 Racks Per Hour
- **0.48 Gallons/Rack With Energy Sentinel** (idle pump shut-off)
- **Advanced Touchscreen Display** intuitive condition alerts, with user friendly cleaning and operation visual guidance, multi-lingual
- **Enhanced Visual On-board Diagnostics** quickly identify machine faults for rapid resolution and less downtime
- **Automatic Tank Fill**
- **Programmable Machine Dwell** pauses rack in wash zone for extended cleaning, NSF Certified Pot & Pan Mode
- **Automatic Drain Valve**
- · Single-Piece Hood Design
- Single-Piece Scrap Screen more robust and faster cleaning
- Single-Piece Stainless Steel Upper And Lower Wash Arm **Manifolds**
- **Single-Point Electrical Connection**
- 20" Standard Vertical Clearance accommodates 18" x 26" sheet pans
- **Fully Insulated Doors** open a full 180° for unrestricted cleaning access
- All Stainless Steel Heavy Gauge Construction including base, legs and feet
- Enclosure Panels (front and sides)
- 2 HP Pump Motor with stainless steel impeller
- **Factory Authorized Start-Up**
- Vent Fan Control
- **ENERGY STAR® Certified**

### **SPECIFIER STATEMENT**

Specified unit will be Champion model 44 PRO Series high temperature rack conveyor dishwashing machine. Features top mounted prodigy HMI user interface controls with proactive maintenance software, proportional rinse, using only 100 GPH, optional built-in 21kW booster, progressive anti-jam drive system, energy sentinel (idle pump shut-off), 209 racks per hour, single-piece hood design, single-piece stainless steel upper & lower wash arms manifolds, full 180° opening leak proof insulated hinged access doors.

#### 1 Year parts and labor warranty.

#### In the USA:

3765 Champion Blvd, Winston-Salem, NC 27105 Tel: (336) 661-1556 Fax: (336) 661-1979 www.championindustries.com

#### In Canada:

2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO Tel: (905) 562-4195 Fax: (905) 562-4618 www.championindustries.com/1canada

ev. 07/2025	Printed in U.S.A.	APPROVAL:	DATE:



# **44 PRO-E**

### HIGH TEMPERATURE ELECTRIC RACK CONVEYOR

#### **ACCESSORIES**

- □ Drain water tempering kit (unmounted)
- ☐ Table limit switch, unmounted (recommended on all rack conveyor installations) (unmounted)
  - o WHISKER STYLE
  - o BUTTON STYLE
- Uent cowl, stainless steel with 7" stacks & locking dampers
- Extended vent cowl, with 7" stacks, locking dampers & external curtain
- ☐ Flanged feet (unmounted)
- □ Water hammer kit (unmounted)
- ☐ Chemical pump kit (detergent and rinse aid, mounted and interwired)
- Water pressure regulating valve (unmounted; standard with booster)
- □ ION scale prevention device (unmounted)
- Water softening system (manufactured, warrantied and serviced by Kinetico)
- ☐ Dish racks:
  - o PEG RACK
  - o FLAT RACK
  - o SHEET PAN RACK
- ☐ Splash shields
- ☐ Cantilever sideloader (without hood)

for 90° load operation

- o 24" SIDELOAD
- o 30" SIDELOAD (ACCEPTS SHEET PANS)
- ☐ Model PRO-90B unloader (90° corner conveyor table)
- ☐ Model PRO-90B loader (90° corner conveyor table)
- ☐ Model RCT 64 or RCT 84 roller conveyor table (see factory for custom length)
- ☐ Stainless steel rear enclosure panels
- □ Correctional package (contact factory)

#### **OPTIONS**

- ☐ Two-point electrical connection, separate for machine and booster (field convertible)
- □ 33" Blower dryer electric
- □ Booster heaters (completely interplumbed, controls are interwired)
  - o 40°F RISE (BUILT-IN) (FIELD CONVERTED)
  - o 70°F RISE (BUILT-IN)
- □ Direct link connectivity solution
- ☐ Direct link plus+ connectivity solution

Cantilever Sideloader (no hood)



**PRO-90B** 

90° Corner Conveyor table loader and unloader available





In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada



# **44 PRO-E**

### HIGH TEMPERATURE ELECTRIC RACK CONVEYOR

#### **UTILITIES**

1	Electrical Connections  Machine electrical connection and booster electrical connection			
2	Hot Water			
	25 PSI flowing pressure (machine with built-in booster) Main connection 1/2" NPT with 110° incoming water (Initial Fill = 17 Gal)			
4	Hot Water			
	20 PSI flowing pressure (machine with no booster) Main connection 1/2" NPT with 180° incoming water (Initial Fill = 17 Gal)			
5A	Drain			
	Connection 1-1/4" NPT Drain Max Flow Rate (g/min) 15			
8	Vents			
	A Stack connection – load end 200 CFM @ 1/4" static pressure			
	B Stack connection – unload end 400 CFM @ 1/4" static pressure			

Warning: Plumbing and electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary, and safety codes and the National Electrical Code.

Note: Water Hammer Arrestor (meeting ASSE-1010 standard or equivalent) to be supplied (by others) in common water supply line at service connection.

**Plumbing Notes:** Because of the variation in house-supplied steam and water pressures, steam and water pressure regulating valves (PRVs) may be needed. (Water PRV is standard on machines with booster.) The PRVs can either be purchased from Champion or obtained locally.

Champion does not endorse using on-demand (tankless) water heating systems, as well as PEX and other plumbing materials that may limit water flow, as these could impair machine performance. For optimal results, we recommend using appropriately sized conventional hot water tanks and standard copper water supply lines that adhere to our specifications. Not following these recommendations may void the manufacturer's warranty.

Water hardness of 3 grains/US Gal (0.83 Imp Gal) - 5.3 Mg/L or less

Venting Notes: Fabricated duct size: 3-7/8" x 15-7/8" (outside dimensions)

Optional Drain Tempering: 1/2" NPT cold water connection required. 1/2" NPT drain connection from back flow preventer to house drain. (FIELD INSTALLED and PLUMBED).

#### **SPECIFICATIONS**

Capacity		
Racks per hr (NSF rated)	209	
Wash tank (US gal.)	17	
Conveyor speed (ft/min)	5.8	
Conveyor speed Pot/Pan Mode (ft/min) (only one rack at a time in pot/pan)	4.5	
Motor Horsepower		
Drive	1/6	
Wash	2	
Water Consumption		
US Gal. per hr (max. use)	100	
US Gal. per rack	0.48	
Heating		
Tank Heat, electric (kW)	15	
Electric booster (built-in) (kW supplied for 40°F rise)	12	
Electric booster (built-in) (kW supplied for 70°F rise)	21	
Booster heaters completely inter plumbed, controls are inte	rwired.	
Venting		
Load end (minimum CFM)	200	
Unload end (minimum CFM)	400	
Standard 20"x 20" Rack Complement		
Peg	1	
Flat	1	

## Single Tank PRO Rack Machine and Booster Ratings

The tables below give the ratings for each model. The ratings include the requirements of the 12 and 21 kW booster heaters when they are in use.

#### Machines with a single point electrical connection:

44 PRO Electric Tank Heat, 21 kW 70° Booster				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	111	150	150	
240/60/3	96	125	125	
480/60/3	47	60	60	
575/60/3	40	50	50	

44 PRO Electric Tank Heat, 12 kW 40° Booster				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	85	110	110	
240/60/3	74	100	100	
480/60/3	36	50	50	
575/60/3	31	40	40	

44 PRO Electric Tank Heat, No Booster				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	52	70	70	
240/60/3	45	60	60	
480/60/3	22	30	30	
575/60/3	19	25	25	

#### Machines with a dual point electrical connection:

44 PRO Electric, 21 kW Booster Only			
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device
208/60/3	59	80	80
240/60/3	51	70	70
480/60/3	26	35	35
575/60/3	22	30	30

44 PRO Electric, 12 kW Booster Only			
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device
208/60/3	34	45	45
240/60/3	29	40	40
480/60/3	15	20	20
575/60/3	12	15	15

#### Note:

Machine ships as a single point electrical connection standard. Easily converted to a dual point connection by a qualified electrician.

In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada




# **44 PRO-E**

### HIGH TEMPERATURE ELECTRIC RACK CONVEYOR


Shipping weight crated: 600 lbs. Dimensions shown in inches

### Front View: Left to Right Model L-R




(5A)4<sup>1</sup>/<sub>4</sub>"


# Front View: Right to Left Model R-L




### Plan View: Left to Right Model





### Plan View: Right to Left Model ◀



#### **End View**







Suggested Table Construction

Flange Details

In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada

Rev. 07/2025 Printed in U.S.A.

Due to an ongoing value analysis program at Champion, specifications contained in this catalog are subject to change without notice.

